

**HORIZONTAL CONDENSERS
WITH PLASTIC CABINET
10000/13000/ 18000/24000 BTU**

HIGHLIGHTS



- Corrosion resistant cabinet
- Quiet
- High efficiency
- High quality



HORIZONTAL CONDENSERS WITH PLASTIC CABINET 10000/13000/18000/24000 BTU

SPECIFICATIONS

MODEL		H10C1PR1	H10C2PR1	H13C1PR1	H13C2PR1	H18C2PR1	H24C2PR1
CAPACITY	Nominal (BTU):	10,000	10,000	13,000	13,000	18,000	24,000
EFFICIENCY	SEER:	11.3	11.3	11.3	11.3	11.3	11.3
FAN	Diameter (in):	15¼	15¼	15¼	15¼	16½	16½
	CFM:	2000	2000	2000	2000	2200	2200
FAN MOTOR	HP:	1/25	1/25	1/25	1/25	1/6	1/6
	RPM:	880	880	880	880	1030	1030
	FLA:	0.40	0.20	0.40	0.20	0.50	0.50
ELECTRICAL	Voltage-Phase-Hertz:	115-1-60	220-1-60	115-1-60		220-1-60	
	Range(volts):	103~127	187 ~ 253V	103~127		187 ~ 253V	
AMPS	Nominal:	8.4	4.5	11.6	6.2	8.8	11.2
	Minimum Circuit:	10	6	15	8	10	15
	Fuse Maximum:	15	10	20	10	15	20
COMPRESSOR	Type:	Rotary					
	RLA:	8.1	4.2	11.3	6.0	8.3	10.7
	LRA:	40	26	56	35	47	56
REFRIGERANT	Type:	R-22					
REFRIGERANT CONNECTIONS	Flare/Sweat:	Flare					
	Liquid (in):	1/4	1/4	1/4	1/4	1/4	3/8
	Suction (in):	3/8	3/8	1/2	1/2	1/2	5/8
UNIT DIMENSIONS	Height (in):	22	22	22	22	24½	24½
	Width (in):	28¼	28¼	28¼	28¼	33¼	33¼
	Depth (in):	10½	10½	10½	10½	13	13
NET WEIGHT	(lbs):	66	66	70	70	93	102
CARTON BOX DIMENSIONS	Height (in):	24½	24½	24½	24½	27¼	27¼
	Width (in):	34	34	34	34	40	40
	Depth (in):	15½	15½	15½	15½	15½	15½
GROSS WEIGHT	(lbs):	76	76	80	80	102	106

- Specifications are subject to change without notice.
- The cooling capacities shown are nominal values based on the standards ARI 210/240: (air Entering) Outdoor unit: 95 °f DB, 75 °f WB, Indoor Unit: 80 °f DB, 67 °F WB. Chosen installation area may affect cooling performance.
- Always consult equipment nameplate for exact electrical requirements.