

PTAC
9000 / 12000 / 15000 BTU

HIGHLIGHTS & SPECS

- Stylish design
- High efficiency
- Heavy duty applications
- Wired digital control
- Digital display
- Typical application: hotel rooms

MODEL		B09C2PR1	B12C2PR1	B15C2PR1
CAPACITY	Nominal (BTU)	9,300	12,600	15,400
EFFICIENCY	SEER	12.0	12.0	12.0
FAN	High	265	310	400
	Airflow (CFM) - Med	235	275	370
	Low	210	245	330
	Air Movement	Manual or Automatic Swing		
CONTROL	Type	Wired Digital Remote		
	Display	Digital		
POWER	Voltage-Phase-Hertz	220 - 1 - 60		
	Range (volts)	197 ~ 253	197 ~ 253	197 ~ 253
	Input Watts	840	1130	1660
	Amps	3.8	5.2	7.2
MOISTURE REMOVAL	(pint/day)	51	74	92
NOISE LEVEL dB(A)	(at High Speed)	44	45	46
COOLING AREA	(ft ²)	95 ~ 150	150 ~ 230	190 ~ 280
REFRIGERANT	Type	R 22		
	Expansion Device	Capillary Tube		
UNIT DIMENSIONS	Height (in)	16	16	16
	Width (in)	42	42	42
	Depth (in)	22	22	22
CARTON BOX DIMENSIONS	Height (in)	17	17	17
	Width (in)	44	44	44
	Depth (in)	23	23	23
WEIGHT	Net / Gross (lbs)	120 / 131	132 / 143	141 / 159
	20 FT	72	72	72
CONTAINER LOADING	40 FT	144	144	144
	40 HQ	190	190	190



- Specifications are subject to change without notice.
- The cooling capacities shown are nominal values based on the standards ARI 210/240: (air Entering) Outdoor unit: 95°F DB, 75°F WB, Indoor Unit: 80°F DB, 67°F WB. Chosen installation area may affect cooling performance.
- Always consult equipment nameplate for exact electrical requirements.