

**FLOOR-CEILING CONSOLES**  
**18000~24000/30000~36000/48000~60000 BTUH**

HIGHLIGHTS

- LCD Remote Control
- Automatic Air Swing
- Alarm Function
- Easy to Install



**FLOOR-CEILING CONSOLES**  
**18000~24000/30000~36000/48000~60000 BTUH**

SPECIFICATIONS

MODEL		U24C2DB3	U36C2DB3	U60C2DB3
<b>CAPACITY</b>	Nominal Btu/h Range	<b>18,000 ~ 24,000</b>	<b>30,000 ~ 36,000</b>	<b>48,000 ~ 60,000</b>
<b>FAN</b>	No of Fans	<b>2</b>	<b>3</b>	<b>4</b>
	Type	<b>Double Inlet Aero Multiblade Centrifugal Blowers</b>		
	Airflow (CFM)	<b>600</b>	<b>800</b>	<b>1600</b>
	Noise Level dB(A)	<b>40</b>	<b>42</b>	<b>46</b>
	Air Movement	<b>Automatic Air Swing</b>		
<b>MOTOR</b>	Motor HP	<b>1/10</b>	<b>1/6</b>	<b>1/10 (2)</b>
	Motor RPM	<b>1550</b>	<b>1550</b>	<b>1550</b>
	Motor Amps	<b>0.7</b>	<b>0.8</b>	<b>0.5 (2)</b>
	Motor Speed	<b>3</b>	<b>3</b>	<b>3</b>
<b>ELECTRICAL</b>	Voltage-Fases-Hertz	<b>220-240-1-60</b>		
	Range	<b>175 - 253</b>		
<b>REFRIGERANT CONNECTION</b>	Flare/Sweat	<b>Flare</b>		
	Refrigerant Control	<b>Accurator - Piston Type</b>		
	Fixed or Removable	<b>Removable</b>		
	Size/Piston No.	<b>0.077</b>	<b>0.086</b>	<b>0.098</b>
	Liquid (In)	<b>3/8</b>	<b>3/8</b>	<b>3/8</b>
	Suction (In)	<b>5/8</b>	<b>3/4</b>	<b>3/4</b>
<b>DRAIN CONN.</b>	Diameter (In)	<b>1</b>		
<b>CONTROL</b>	Remote Control	<b>Yes, Wireless with LCD Display</b>		
	Auto Restart	<b>Yes</b>		
	Protection	<b>Time Delay</b>		
<b>UNIT DIMENSIONS</b>	Height (In)	<b>26</b>	<b>26</b>	<b>26¾</b>
	Width (In)	<b>38½</b>	<b>50¼</b>	<b>66</b>
	Depth (In)	<b>7¾</b>	<b>7¾</b>	<b>9½</b>
<b>CARTON BOX DIMENSIONS</b>	Height (In)	<b>26½</b>	<b>26½</b>	<b>27¼</b>
	Width (In)	<b>42½</b>	<b>52½</b>	<b>66½</b>
	Depth (In)	<b>8½</b>	<b>8½</b>	<b>10</b>
<b>WEIGHT</b>	Shipping (Lbs)	<b>67</b>	<b>86</b>	<b>125</b>

Notes: Specifications are subject to change without notice. The cooling capacities shown are nominal values based on the standards ARI 210/240: (air entering) Outdoor unit: 95°F DB, 75°F WB, Indoor Unit: 80°F DB, 67°F WB. Chosen installation area may affect cooling performance. Always consult equipment nameplate for exact electrical requirements. Fan-Coil units are made to match with a variety of outdoor units; Mismatching to unauthorized units will void any warranty